


DESCRIPTIVE FEATURES

- INSULATION THICKNESS 80 MM
- 7" TOUCH SCREEN WITH RECIPE MEMORY
- USB SOCKET FOR DATA DOWNLOAD
- AISI 304 STAINLESS STEEL
- ROUNDED EDGES
- EASILY ACCESSIBLE MAINTENANCE COMPARTMENT
- EVAPORATOR WITH CATAPHORESIS TREATMENT
- ADJUSTABLE FEET
- BOTTOM DRAIN WITH STANDARD COLLECTION TRAY
- RIGHT HINGE AS STANDARD (LEFT HINGE ON REQUEST)
- REFRIGERANT GAS R452A (ON REQUEST R448A, R449A)
- BIVALENT TRAY SUPPORT GN 1/1 OR EN 60X40
- DISTANCE BETWEEN RACK RAILS 65 mm

ACCESSORIES


ACC 509
Heated core probe



ACC 510
Multipoint core probe




ACC 110
Ozone sterilizer




ACC 141
Kit 4 Castors



ACC 135
Door Opening Left



ACC 148
Led Light



ACC 800/3
Surcharge for EN 60X40
Trays Holder



Special voltages on
request



ACC 125
Wi-Fi connection kit



ACC 126
Connection to the
Sinofcold Cloud,
valid for 3 years

ROOM CONDITIONS

+32°C

60% UR

SPECIFICATIONS IN COMPLIANCE WITH prEN 17032

Blast Chilling (+65°C / +10°C)		Deep Freezing (+65°C / -18°C)	
Max. Capacity	Time	Max. Capacity	Time
40 kg	120 min	25 kg	260 min

CONSUMPTION (prEN 17032)

Blast Chilling	Deep Freezing
+90°C / +3°C	+90°C / -18°C
0,10 kWh/kg	0,30 kWh/kg

REFRIGERANT GAS

Type	GWP	Charge
R452A	2141	2 kg
R448A	1387	2 kg
R449A	1397	2 kg

TECHNICAL DATA

Model	FT10.40	FT10.40W	FT10.40R	FT10.40WR	FT10.40SG
Version	AIR	WATER	REMOTE	WATER REMOTE	WITHOUT GROUP
Capacity	10 GN 1/1 (10 EN 60X40)	10 GN 1/1 (10 EN 60X40)	10 GN 1/1 (10 EN 60X40)	10 GN 1/1 (10 EN 60X40)	10 GN 1/1 (10 EN 60X40)
Blast Chilling	40 kg +90°C → +3°C 90 min	40 kg +90°C → +3°C 90 min	40 kg +90°C → +3°C 90 min	40 kg +90°C → +3°C 90 min	40 kg +90°C → +3°C 90 min
Deep Freezing	25 kg +90°C → -18°C 240 min	25 kg +90°C → -18°C 240 min	25 kg +90°C → -18°C 240 min	25 kg +90°C → -18°C 240 min	25 kg +90°C → -18°C 240 min
Standard tension	400 V / 3 Ph+N 50 Hz	400 V / 3 Ph+N 50 Hz	400 V / 3 Ph+N 50 Hz	400 V / 3 Ph+N 50 Hz	400 V / 3 Ph+N 50 Hz
Power consumption	2,0 kW / 6,5 A	2,0 kW / 6,5 A	2,0 kW / 6,5 A	2,0 kW / 6,5 A	1,0 kW / 4,0 A
HP	2,0 HP	2,0 HP	2,0 HP	2,0 HP	•
Noise	<70 dB	<70 dB	<70 dB	<70 dB	<70 dB
Refrigeration power -10°C	3.900 W Evap. -10°C Cond. +45°C	3.900 W Evap. -10°C Cond. +45°C	3.900 W Evap. -10°C Cond. +45°C	3.900 W Evap. -10°C Cond. +45°C	•
Refrigeration power -30°C	1.400 W Evap. -30°C Cond. +45°C	1.400 W Evap. -30°C Cond. +45°C	1.400 W Evap. -30°C Cond. +45°C	1.400 W Evap. -30°C Cond. +45°C	•
Dimensions	798 x 853 x 1480/1520 mm	798 x 853 x 1480/1520 mm	798 x 853 x 1480/1520 mm	798 x 853 x 1480/1520 mm	798 x 853 x 1480/1520 mm
Net Weight	170 kg	170 kg	170 kg	170 kg	120 kg
Set-up	PURE KLIMA EXPERIENCE	PURE KLIMA EXPERIENCE	PURE KLIMA EXPERIENCE	PURE KLIMA EXPERIENCE	PURE

