


DESCRIPTIVE FEATURES


- INSULATION THICKNESS 70 mm
- 7" TOUCH SCREEN WITH RECIPE MEMORY
- USB SOCKET FOR DATA DOWNLOAD
- AISI 304 STAINLESS STEEL
- ROUNDED EDGES
- EASILY ACCESSIBLE MAINTENANCE COMPARTMENT
- EVAPORATOR WITH CATAPHORESIS TREATMENT
- ADJUSTABLE FEET
- BOTTOM DRAIN WITH STANDARD COLLECTION TRAY
- RIGHT HINGE AS STANDARD (LEFT HINGE ON REQUEST)
- REFRIGERANT GAS R452A (ON REQUEST R448A, R449A)
- BIVALENT TRAY SUPPORT GN 1/1 OR EN 60X40
- DISTANCE BETWEEN RACK RAILS 65 mm

ACCESSORIES



ACC 509
Heated core probe




ACC 510
Multipoint core probe



ACC 110
Ozone sterilizer



ACC 154
Rails For
Rational Oven



ACC 155
Rails For Oven




ACC 140
Kit 4 Castors



ACC 135
Door Opening Left



ACC 147
Led Light



ACC 800/1
Surcharge for EN 60X40
Trays Holder



Special voltages on
request



ACC 125
Wi-Fi connection kit



ACC 126
Connection to the
Sinofcold Cloud,
valid for 3 years

ROOM CONDITIONS

+32°C

60% UR

SPECIFICATIONS IN COMPLIANCE WITH prEN 17032

Blast Chilling (+90°C / +3°C)		Deep Freezing (+90°C / -18°C)	
Max. Capacity	Time	Max. Capacity	Time
20 kg	120 min	12 kg	260 min

CONSUMPTION (prEN 17032)

Blast Chilling	Deep Freezing
+90°C / +3°C	+90°C / -18°C
0,12 kWh/kg	0,40 kWh/kg

REFRIGERANT GAS

Type	GWP	Charge
R452A	2141	1 kg
R448A	1387	1 kg
R449A	1397	1 kg

TECHNICAL DATA

Model	FT5.20	FT5.20W	FT5.20R	FT5.20WR	FT5.20SG	FT5.20SGCO ₂
Version	AIR	WATER	REMOTE	WATER REMOTE	WITHOUT GROUP	WITHOUT ROUP (CO ₂)
Capacity	5 GN 1/1 5 EN 60X40	5 GN 1/1 5 EN 60X40	5 GN 1/1 5 EN 60X40	5 GN 1/1 5 EN 60X40	5 GN 1/1 5 EN 60X40	5 GN 1/1 5 EN 60X40
Blast Chilling	20 kg +90°C → +3°C 90 min	20 kg +90°C → +3°C 90 min	20 kg +90°C → +3°C 90 min	20 kg +90°C → +3°C 90 min	20 kg +90°C → +3°C 90 min	20 kg +90°C → +3°C 90 min
Deep Freezing	12 kg +90°C → -18°C 240 min	12 kg +90°C → -18°C 240 min	12 kg +90°C → -18°C 240 min	12 kg +90°C → -18°C 240 min	12 kg +90°C → -18°C 240 min	12 kg +90°C → -18°C 240 min
Standard tension	230 V / 1 Ph 50 Hz	230 V / 1 Ph 50 Hz	230 V / 1 Ph 50 Hz	230 V / 1 Ph 50 Hz	230 V / 1 Ph 50 Hz	230 V / 1 Ph 50 Hz
Power consumption	1,3 kW / 7,0 A	1,3 kW / 7,0 A	1,3 kW / 7,0 A	1,3 kW / 7,0 A	0,6 kW / 3,5 A	0,6 kW / 3,5 A
HP	1,1 HP	1,1 HP	1,1 HP	1,1 HP	•	•
Noise	<70 dB	<70 dB	<70 dB	<70 dB	<70 dB	<70 dB
Refrigeration power -10°C	1.750 W Evap. -10°C Cond. +45°C	1.750 W Evap. -10°C Cond. +45°C	1.750 W Evap. -10°C Cond. +45°C	1.750 W Evap. -10°C Cond. +45°C	1.750 W Evap. -10°C Cond. +45°C	1.750 W Evap. -10°C Cond. +45°C
Refrigeration power -30°C	1.750 W Evap. -30°C Cond. +45°C	1.750 W Evap. -30°C Cond. +45°C	1.750 W Evap. -30°C Cond. +45°C	1.750 W Evap. -30°C Cond. +45°C	1.750 W Evap. -30°C Cond. +45°C	1.750 W Evap. -30°C Cond. +45°C
Dimensions	798 x 737 x 835/865 mm	798 x 737 x 835/865 mm	798 x 737 x 835/865 mm	798 x 737 x 835/865 mm	798 x 737 x 835/865 mm	798 x 737 x 835/865 mm
Net Weight	105 kg	105 kg	105 kg	105 kg	75 kg	75 kg
Set-up	PURE KLIMA EXPERIENCE	PURE KLIMA EXPERIENCE	PURE KLIMA EXPERIENCE	PURE KLIMA EXPERIENCE	PURE KLIMA EXPERIENCE	PURE

